

Exhaust Valve

◆ Product Description

The special DN25 exhaust valve for the pipeline system can quickly exhaust the air in the pipeline to prevent air blockage. It is tightly sealed and corrosion-resistant to ensure the normal operation of the pipeline.



◆ Product Advantages

- Efficient exhaust,
- Tight sealing,
- Strong corrosion resistance,
- Easy installation
- Long service life

◆ Product Structure

It is made of brass/cast iron, with built-in floating ball opening and closing structure, standardized interface design, and anti-rust and anti-corrosion treatment of the valve body.

◆ Technical Features

Specification: DN25
 Material: brass/cast iron
 Working pressure: 0.1-1.6MPa
 Working temperature: -10 °C ~ 120 °C
 Connection method: thread/flange
 Sealing class: GB/T 13927 -2008

Material Code	Weight	packing
1.4.24.01.0947	0.4kg	1Pcs

◆ Application Scenarios

Water supply and drainage pipeline, HVAC system, industrial fluid pipeline, municipal pipe network, building water supply and drainage engineering.

◆ Remarks

HORB has a technical hotline for technical and usage inquiries. This information is deemed accurate, for professional end users only. HORB data is for reference.
 KANBO is a registered trademark of HORB®. All Rights Reserved.