

Tin Bar

◆ Product Description

The floor air shower transfer window is specially used in the clean area. The air shower has good dust removal effect. The interlocking sealing design prevents cross contamination. The structure is firm and the operation is simple. It is suitable for material transfer in the clean area.



◆ Product Advantages

- Efficient dust removal by air shower
- Mechanical interlock to prevent pollution
- Excellent sealing performance
- Firm and durable structure
- Simple and convenient operation

◆ Product Structure

304 stainless steel integral welding, built-in high-efficiency air shower system, double-door mechanical interlocking structure, sealing strip protection, rounded corner design, built-in lighting and sterilization

◆ Technical Features

Material: 304 stainless steel
 Internal size 1200 * 800 * 800 mm,
 Wind speed ≥ 25m/s
 Filtration efficiency ≥ 99.97%,
 Interlocking mode: mechanical interlocking
 Working voltage:220V

Item#	Weight	Packing
1.4.21.00.0002	120 kg	Individually wrapped

◆ Application Scenarios

Material transfer in electronic dust-free workshop, medical clean area, food processing clean workshop, semiconductor workshop and laboratory clean area

◆ Remarks

HORB has a technical hotline for technical and usage inquiries. This information is deemed accurate, for professional end users only. HORB data is for reference.
 KANBO is a registered trademark of HORB®. All Rights Reserved.