

Automatic Drain Valve

◆ Product Description

Automatic drain valve, air intake 1/2 "external thread, drainage 3/8" internal thread, automatic drainage of condensate, precise drainage, leak-proof sealing, temperature and corrosion resistance, suitable for pneumatic compressed air system.



Product Advantages

- Automatic drainage without duty
- Special thread specification
- Precise drainage without waste
- Sealing, leak-proof and anti-corrosion
- Adapted to the pneumatic system

◆ Product Structure

Aluminum alloy valve body, floating-ball automatic control structure, 1/2 "external thread inlet, 3/8" internal thread outlet, high sealing valve core, surface oxidation treatment.

◆ Application Scenarios

Automatic discharge of condensed water from air compressor system, pneumatic equipment pipeline, compressed air station, freeze dryer and air storage tank.

◆ Technical Features

Valve body material: aluminum alloy
 Air inlet: 1/2 "external thread
 Water outlet: 3/8" internal thread
 Working pressure: 0.2-1.0 MPa
 Working temperature: 0 ~ 60 °C
 Drainage accuracy: ± 2 mm
 Adaptive medium: condensed water/compressed air

Item#	size	Weight
1.4.24.01.0056	1/2"-3/8"	0.3kg

◆ Remarks

HORB has a technical hotline for technical and usage inquiries. This information is deemed accurate, for professional end users only. HORB data is for reference.
 KANBO is a registered trademark of HORB®. All Rights Reserved.